


SHEARS / STAHLSCHEREN

HSS SERIES

 14 MODELS SCRAP / STEEL SHEARS FROM 300 UP TO 21.850 KGS FOR EXCAVATORS FROM 4 ~ 280 TONS

 14 MODELLE STAHLSCHEREN VON 300 BIS ZU 21.850 KG FÜR BAGGER VON 4 BIS 280 TONNEN



			HSS-3RV	HSS-6RV	HSS-10RV	HSS-14RV	HSS-22RV	HSS-28RV	HSS-34RV	HSS-45RV	HSS-52RV	HSS-62RV	HSS-82RV	HSS-110RV	HSS-180RV	HSS-220RV
 (1)	Baggerklasse/Excavatorclass	T.	4 : 5	5 : 8	8 : 12	12 : 18	18 : 23	23 : 30	30 : 38	40 : 50	52 : 65	55 : 70	75 : 100	120 : 150	140 : 210	200 : 280
	Gewicht / Weight	Kg.	300	610	1020	1360	2180	2840	3360	4380	5160	6480	8230	11680	18340	21850
	Maulweite / Jaw opening	mm.	265	340	405	475	535	575	615	680	730	780	845	920	1100	1180
	Maultiefe / Jaw depth	mm.	230	320	355	385	445	495	545	600	640	690	710	780	1080	1130
	Arbeitsdruck / Workingpressure	Bar	220	300	380	380	380	380	380	380	380	380	380	380	380	380
	Ölvolumenstrom / Oilflow	L/min.	80/100	80/150	100/150	150/250	180/250	200/300	200/300	300/400	350/450	400/500	450/600	500/800	700/1000	900/1200
	Drehbar / Rotatable															
	Arbeitsdruck beim rotieren / Workingpressure rotation	Bar	120	120	120	180	180	180	180	180	180	180	180	180	180	180
	Ölvolumenstrom beim rotieren / Oilflow rotation	L/min.	5	10	10	10	10	10	10	10	10	10	10	50	50	50
	Öffnen/Schließen (sek.) / Open/close (sec.)	Sec.	1.0/2.8	1.0/2.0	1.9/3.6	1.9/2.5	2.0/2.8	2.9/2.9	3.9/4.1	3.4/4.0	3.2/4.0	3.0/4.1	3.8/4.7	4.2 / 5.1	4.6/5.3	4.8/5.8

(1) Recommended excavator / attachment combination

(1) Empfohlene Bagger/Anbauteil Kombination

